IN THE CLAIMS:

Please amend Claims 1-4, 7-11, 13, 14, and 16-19 as follows.

1. (Currently Amended) An image processing apparatus for process image data in which additional information is embedded, comprising:

input means for inputting <u>original</u> image data showing an original image, <u>wherein</u> the <u>original</u> image data is constructed by a plurality of bit planes;

compressing means for compressing the image data at a position where the additional information is embedded data of at least a first predetermined bit plane of the original image data to form compression data; and

first embedding means for embedding the compression data obtained by said compressing means into the image data the first predetermined bit plane of the original image data.

- 2. (Currently Amended) An apparatus according to claim 1, wherein the image data is constructed by a plurality of bit planes and the first embedding means embeds the compression data to the first predetermined bit plane is a lower bit plane.
- 3. (Currently Amended) An apparatus according to claim 1, further comprising wherein said compressing means comprises second embedding means for embedding the additional information into the image data at a position different from the position where the additional information is originally embedded the data of the first predetermined bit plane and

data of a second predetermined bit plane of the original image data, and further embedding additional information into the second predetermined bit plane.

- 4. (Currently Amended) An apparatus according to claim 3, wherein the image data is constructed by a plurality of bit planes and said second embedding means embeds the additional information to the second predetermined bit plane is an upper bit plane.
 - 5. (Cancelled)
 - 6. (Cancelled)
- 7. (Currently Amended) An apparatus according to claim 1, wherein said <u>original</u> image data comprises color components of RGB.
- 8. (Currently Amended) An image processing method for processing image data in which additional information is embedded, comprising:

an input step of inputting the <u>original</u> image data representing an original image, wherein the original image data is <u>constructed by a plurality of bit planes</u>;

a compressing step of compressing the image data at a position where the additional information is embedded data of at least a first predetermined bit plane of the original image data to form compression data; and

a first embedding step of embedding the compression data obtained in the compressing step into the image data the first predetermined bit plane of the original image data.

9. (Currently Amended) A storage medium which stores an image processing program so that it can be read out by a computer, wherein said program processes image data in which additional information is embedded and comprises:

an input step of inputting the <u>original</u> image data showing an original image, wherein the <u>original</u> image data is constructed by a plurality of it planes;

a compressing step of compressing the image data at a position where the additional information is embedded data of at least a first predetermined bit plane of the original image data to form compression data; and

a first embedding step of embedding the compression data obtained in the compressing step into the image data the first predetermined bit plane of the original image data.

10. (Currently Amended) An image processing apparatus comprising:

input means for inputting original image data showing an original image, wherein the original image data is constructed by a plurality of bit planes;

compression means for compressing image data, wherein the image data

compressed by said compression means includes at least data at a second predetermined bit

position data of a first predetermined bit plane and data of a second predetermined bit plane of the

original image data to form compression data;

first embedding means for embedding the data compressed by the compressing means to a first predetermined bit position of the image data into the first predetermined bit plane of the original data; and

second embedding means for embedding additional information to the second predetermined bit position into the second predetermined bit plane of the original image data.

- 11. (Currently Amended) An apparatus according to claim 10, further comprising holding means for holding information representing the first predetermined bit position plane, as key information.
- 12. (Original) An apparatus according to claim 10, wherein the compression by said compressing means is a reversible compression.
- 13. (Currently Amended) An image processing apparatus comprising:

 input means for inputting original image data showing an original image, wherein
 the original image data is constructed by a plurality of bit planes;

compressing means for compressing image data, wherein the image data

compressed by said compression means includes at least data at a second predetermined bit

position data of a first predetermined bit plane and data of a second predetermined bit plane of the

original image data to form compression data;

encrypting means for encrypting data showing a result of the compression in said compressing means;

first embedding means for embedding the data compressed encrypted by the encrypting means to a first predetermined bit position of the image into the first predetermined bit plane of the original image data; and

second embedding means for embedding additional information to the second predetermined bit position into the second predetermined bit plane of the original image data.

- 14. (Currently Amended) An apparatus according to claim 13, further comprising holding means for holding information representing the first predetermined bit position plane, as key information.
- 15. (Original) An apparatus according to claim 13, wherein the compression by said compressing means is a reversible compression.
- 16. (Currently Amended) An image processing method comprising:

 input means for inputting original image data showing an original image, wherein the original image data is constructed by a plurality of bit planes;

by said compressing step includes at least data at a second predetermined bit position data of a first predetermined bit plane and data of a second predetermined bit plane of the original image data to form compression data;

a first embedding step of embedding the data compressed by the compressing step to a first predetermined bit position of the image into the first predetermined bit plane of the original image data; and

a second embedding step of embedding additional information to the second predetermined bit position into the second predetermined bit plane of the original image data.

17. (Currently Amended) An image processing method comprising:

input means for inputting original image data showing an original image, wherein the original image data is constructed by a plurality of bit planes;

by said compressing step includes at least data at a second predetermined bit position data of a first predetermined bit plane and data of a second predetermined bit plane of the original image data to form compression data;

an encrypting step of encrypting data showing a result of the compression in said compressing step;

a first embedding step of embedding the data compressed encrypted by the encrypting step to a first predetermined bit position of the image into the first predetermined bit plane of the original image data; and

a second embedding step of embedding additional information to the second predetermined bit position into the second predetermined bit plane of the original image data.

18. (Currently Amended) A computer-readable storage medium which stores a program for executing an image processing method, wherein said method comprises:

input means for inputting original image data showing an original image, wherein the original image data is constructed by a plurality of bit planes;

by said compressing step includes at least data at a second predetermined bit position data of a first predetermined bit plane and data of a second predetermined bit plane of the original image data to form compression data;

a first embedding step of embedding the data compressed by the compressing step to a first predetermined bit position of the image into the first predetermined bit plane of the original image data; and

a second embedding step of embedding additional information to the second predetermined bit position into the second predetermined bit plane of the original image data.

19. (Currently Amended) A computer-readable storage medium which stores a program for executing an image processing method, wherein said method comprises:

input means for inputting original image data showing an original image, wherein the original image data is constructed by a plurality of bit planes;

by said compressing step includes at least data at a second predetermined bit position data of a first predetermined bit plane and data of a second predetermined bit plane of the original image data to form compression data;

an encrypting step of encrypting data showing a result of the compression in said compressing step;

a first embedding step of embedding the data compressed encrypted by the encrypting step to a first predetermined bit position of the image into the first predetermined bit plane of the original image data; and

a second embedding step of embedding additional information to the second predetermined bit position into the second predetermined bit plane of the original image data.

- 20. (Previously Presented) An apparatus according to claim 1, wherein the compression by the compressing means is reversible compression.
- 21. (Previously Presented) An apparatus according to claim 1, wherein the first embedding means embeds the data as an invisible watermark.
- 22. (Previously Presented) An apparatus according to claim 11, wherein the first embedding means embeds the data as an invisible watermark, and the second embedding means embeds the additional information as a visible watermark.